



HMIS RATINGS:  
Health: 2  
Flammability: 4  
Reactivity: 0  
Personal Protection: G

---

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Dynamite Oven Cleaner

Emergency Telephone Number: (800)535-5053

Chemical Family: Aerosol

Date Prepared: April 25, 2003

Company Identification: ROADRUNNER INDUSTRIES, INC.

MSDS Number: RR-A150

P.O. BOX 16247

ATLANTA, GA. 30321

---

## Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

| CAS<br>NUMBER | CHEMICAL<br>NAME   | % BY<br>WGHT. | OSHA PEL/<br>ACGIH TLV   | SARA<br>302/<br>304(1)* | SARA<br>313<br>(2)* | STATE<br>INFO(3)(4) | CERCLA<br>(4) |
|---------------|--------------------|---------------|--------------------------|-------------------------|---------------------|---------------------|---------------|
| 1310-73-2     | Sodium Hydroxide   | < 5.0         | 2 mg/m3 /<br>2 mg/m3     | NO                      | NO                  | YES(4)              | 1000 lbs      |
| 111-76-2      | 2-Butoxyethanol    | < 2.0         | 25ppm-skin<br>25ppm-skin | NO                      | YES                 | NO                  | None          |
| -             | Propellant Mixture | -             | -                        | -                       | -                   | -                   | -             |
| 74-98-6       | Propane            | -             | 1000 ppm                 | NO                      | NO                  | NO                  |               |
| 106-97-8      | N-Butane           | -             | 600 ppm                  | NO                      | NO                  | NO                  |               |

\* See Section 15 for more information

n/e = none established - n/a = not applicable

---

## Section 3: HAZARDS IDENTIFICATION

## EMERGENCY OVERVIEW

DANGER. Corrosive. Eye and skin irritant. Harmful if swallowed. Avoid breathing vapors. Contents under pressure. Do not puncture or incinerate container.  
Keep away from heat and flames.

---

Primary Route of Entry: Skin contact/absorption, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation, experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling.

INHALATION: High vapor/aerosol concentrations (>1000ppm) are irritating to the respiratory tract.

INGESTION: May cause headache, dizziness, incoordination, nausea, vomiting, diarrhea and general weakness.

## Section 3: HAZARDS IDENTIFICATION - continued:

Chronic / Long Term Effects: 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and secondary injury to the liver and kidney.

Signs and Symptoms of Overexposure: Dermal exposure may cause local redness and swelling, pain and discomfort. Prolonged skin contact may result in absorption of harmful amounts.

Target Organ Effects: Liver, kidney

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

---

## Section 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Seek medical attention immediately. Call a poison control center or doctor for treatment advice. Have person drink large quantities of water if able to swallow. Do not induce vomiting. Do not leave unattended.

---

## Section 5: FIRE FIGHTING MEASURES

Flash Point: No flash by standard methods. Flame Extension: None

Extinguishing Media: Use appropriate methods for combating surrounding fire.

Special Fire Fighting Instructions: CAUTION. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

---

## Section 6: ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

---

## Section 7: HANDLING AND STORAGE

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

## Section 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required, use an organic vapor & particulate cartridge. All respiratory programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

Engineering Controls: Good general ventilation required.

---

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Slightly cloudy, colorless spray with mild odor

pH Concentrate: > 13.0

Solubility in Water: Complete

Vapor Pressure [mmHg]: n/e

Evaporation Rate (Butyl Acetate=1): n/e

Vapor Density [Air=1]: n/e

Specific Gravity [H2O=1]: 1.06

Boiling Point: 212 F

---

## Section 10: REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to avoid: High temperature

Hazardous Decomposition Products: CO, CO2

Incompatibility: Acids, oxidizers, aluminum, painted surfaces, asphalt tile

---

## Section 11: TOXICOLOGICAL INFORMATION

2-Butoxyethanol: SKIN-Rabbit; 24 hr. uncovered-minimal erythema in 2/5; no irritation 3/5

---

## Section 12: ECOLOGICAL INFORMATION

2-Butoxyethanol: Toxicity to fish-fathead minnow; 96h; LC50 Results: 1700 mg/l

---

## Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

---

## Section 14: TRANSPORTATION INFORMATION

D.O.T. Shipping Name / Class:

Consumer Commodity, ORM-D

(Domestic Ground Shipments)

## Section 15: REGULATORY INFORMATION

## U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire ( ) Pressure (X) Reactive ( ) Not Applicable ( )

(1) Title III Section 302/304 Extremely Hazardous Substances - 40 CFR 355 Appendix A

(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s)  
D002

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

(3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)

(4) Massachusetts (Hazardous Substance Disclosure by Employers)

---

## Section 16: OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.