Page 1 of 4

HMIS RATINGS: Health: 2 Flammability: 4 Reactivity: 0 Personal Protection: G

MATERIAL SAFETY DATA SHEET



Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Scratch Off Graffiti Remover Chemical Family: Aerosol Company Identification: ROADRUNNER INDUSTRIES, INC. P.O. BOX 16247 ATLANTA, GA. 30321 Emergency Telephone Number: (800)535-5053 Date Prepared: April 25, 2003 MSDS Number: RR-A200

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS	CHEMICAL	% BY	OSHA PEL/	SARA 302/	SARA 313	STATE	CERCLA
NUMBER	NAME	WGHT.	ACGIH TLV	304(1)*	(2)*	INFO(3)(4)	RQ
108-88-3	Toluene	< 31.0	100 ppm	NO	YES	YES(3)(4)	1000 lbs
67-64-1	Acetone	< 27.0	750 ppm /	NO	NO	NO	5000 lbs
			500 ppm				
111-76-2	2-Butoxyethanol	< 8.0	25ppm-skin	NO	YES	NO	None
78-93-3	Methyl Ethyl Ketone	< 24.0	200 ppm /	NO	YES	NO	5000 lbs
			200 ppm				
-	Propellent Mixture	-	-	-	-	-	
74-98-6	Propane	-	1000 ppm	NO	NO	NO	
106-97-8	N-Butane	-	600 ppm	NO	NO	NO	
* See Section 15 for more information $n/e = none = n/a = not = not = n/a = n/a = not = n/a = n$						plicable	

Section 3: HAZARDS IDENTIFICATION

## EMERGENCY OVERVIEW

DANGER. Extremely flammable. Harmful or fatal if swallowed. Aspiration hazard. Vapor harmful. Harmful to skin. Can cause nervous system depression. Keep away from heat and flame. Contents under pressure. Do not puncture or incinerate container.

Primary Route of Entry: Skin contact/absorption, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation, experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva. Vapors may irritate eyes.

SKIN: Prolonged or repeated contact may cause skin irritation, possible burn or absorption of harmful amounts.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

MSDS Number: RR-A200

#### Section 3: HAZARDS IDENTIFICATION - continued:

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Signs and Symptoms of Overexposure: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Liver, kidneys, lungs

Reproductive/Developmental Information: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Section 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 0 deg. F (TCC Method). Flame Extension: >18", Positive Flashback Extinguishing Media: Dry chemical, CO2 or foam is recommended. Special Fire Fighting Instructions: EXTREMELY FLAMMABLE. Contents under pressure. Cool exposed containers with water spray to prevent bursting. SCBA should be used whenever chemical fires are present.

Section 6: ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

## Section 7: HANDLING AND STORAGE

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

MSDS Number: RR-A200

Section 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear, colorless spray/mist with solvent odor pH Concentrate: n/a Solubility in Water: Negligible Vapor Pressure [mmHg]: n/e Evaporation Rate (Butyl Acetate=1): n/e Vapor Density [Air=1]: n/e Specific Gravity [H20=1]: 0.83 Boiling Point: n/a

### Section 10: REACTIVITY

Stability: Stable Hazardous Polymerization: Will not occur Conditions to avoid: High temperature Hazardous Decomposition Products: CO, CO2 Incompatibility: Acids and strong oxidizers

Section 11: TOXICOLOGICAL INFORMATION

2-Butoxyethanol: SKIN-Rabbit; 24 hr. uncovered-minimal erythema in 2/5; no irritation 3/5

# Section 12: ECOLOGICAL INFORMATION

2-Butoxyethanol: Toxicity to fish-fathead minnow; 96h; LC50 Results: 1700 mg/l

### Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

# Section 14: TRANSPORTATION INFORMATION

D.O.T. Shipping Name / Class:

Consumer Commodity, ORM-D

(Domestic Ground Shipments)

Page 3 of 4

MSDS Number: RR-A200

### Section 15: REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2: ACUTE (X) Chronic (X) Fire (X) Pressure (X) Reactive ( ) Not Applicable ( )

(1) Title III Section 302/304 Extremely Hazardous Substances - 40 CFR 355 Appendix A

(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s) D001

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations. (3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986) (4) Massachusetts (Hazardous Substance Disclosure by Employers)

### Section 16: OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.